



18.0 TRAFFIC CONTROL PLANS

- 18.1 Alternate traffic control plans may be presented to the SHA District Office for approval in conformance with Section 104.01 of the Standard Specifications for Construction and Materials.
- 18.2 For emergency repair operations, a lesser number of traffic control devices (TCDs) than the full compliment may be used. This generally will consist of one sign per direction, flashing lights on the vehicle, and minimum number of channelizing devices, flags, or high level warning devices. Additional TCDs such as arrow panel(s), additional signing, etc., shall be placed as soon as possible in accordance with the standard TTCTA.
- 18.3 Where closely spaced work zones create conflicting traffic patterns (e.g. left-lane closure followed by right-lane closure), they should be no closer than 1.5 miles apart (last sign to first sign). Where work zones are closely spaced, but where traffic patterns are not significantly altered and no conflicts exist, no minimum spacing is required; however, care should be exercised to present appropriate and non-conflicting guidance to the public.
- 18.4 All signs, channelizing devices, and other traffic control devices shall be in conformance with the latest edition of the MUTCD.

SPECIFICATION	CATEGORY CODE ITEMS	Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES GENERAL NOTES STANDARD NO. MD 104.00-18		
APPROVED	 DIRECTOR - OFFICE OF TRAFFIC AND SAFETY			
	APPROVAL • SHA REVISIONS			APPROVAL • FEDERAL HIGHWAY ADMINISTRATION
	APPROVAL 8-20-03			APPROVAL 9-23-03
	REVISED	REVISED		
	REVISED	REVISED		
	REVISED	REVISED		